

Reyee Wireless Overview

Leo Sun 2023-01-31



Contents

Reyee Wireless Naming Rule & Family


Reyee Wireless Product Introduction

Reyee Wireless Key Value

Reyee Wireless Mapping Sale Guide



Reyee AP Naming Rule





Specific Instructions


Se	eries	Ιι	nstallation Method	R	adio Amount		stallation cenario		Case Shape	((Grade By Spatial Stream & Rate)		Key Feature
RAP	Reyee AP	1	Wall-Mount	1	Single-Band	0	WiFi5	0	Square		G	General WiFi5 1*1 BW80 AC733 WiFi6 2*2 BW80 AX1775	F	Fast Ethernet
		2	Ceiling	2	Dua1-Band	6	WiFi6	2	Ball	To Be I		Mainstream / Typical WiFi5 2*2 BW80 AC1267 WiFi6 2*2 BW160 AX2975	Р	PoE out
		6	Outdoor	3	Tri-Band			6	Circular	Removed	Е	Enhance WiFi5 2*2 BW80 AC1267 WiFi6 4*4 BW80 AX3202		хошо у са
											Н	High Grade WiFi5 3*3 BW80 AC1750 WiFi6 4*4 BW160 AX5951		

Remark:

- 1. The brackets will be removed.
- 2 In principle, only one letter will be used for grade & key feature.



Reyee Wi-Fi 7 AP Naming Rule



Specific Instructions of Wi-Fi 7 AP

S	eries		Vi-Fi Gen	Rad	dio Amount		Product Grade (Speed & MIMO)		Additional Spec
RAP	Reyee AP	7	Wi-Fi7	2	Dual-Band		Cost-effective	(Blank)	Ceiling AP
				3	Tri-Band	(Blank)	Entry Level (Full 2x2 MIMO)	-OD	Outdoor AP Omni-Directional Ant.
				4	4 - Band	Pro	Higher Speed, Better Density (Partial 3x3/4x4 MIMO)	-CD	Outdoor AP Directional Ant.
						HD	High Density (Full 4x4 MIMO)	-W	Wall AP
						MAX	Extreme Performance (Full 8x8 MIMO)	-WP	Wall AP with PoE Out





Reyee Wireless Family

Wall

• AX6000 • AX6000 • 2 x 2.5 GE • 2.5 GE, SFP *2.5 GE, SF *130 Users • 130 Users **AX6000** 4x4 MIMO 4x4 MIMO **RAP2260(H)** • AX3200 • 2.5 GE •1 GE AX3200 • 120 Users • 4x4 MIMO **RAP2260(E)** AX3000 • AX3000 • 2.5 GE •1 GE •1 GE, 1 SFP **AX3000** • 110 Users • 110 Users • 2x2 MIMO • 2x2 MIMO **RAP6262 RAP2260** • AX1800 • AX1800 • AX1800 • 2 GE •1 GE. 1 SFP • 2 GE • 100 Users **AX1800** • 100 Users • 100 Users • 2x2 MIMO • 2x2 MIMO • 2x2 MIMO **RAP2260(G) RAP6262(G) RAP6260(G)** • AC1300 • AC1300 • AC1300 • AC1300 • 1 GE WAN • 2 FE • 2 GE • 1 FE WAN • 4 GE LAN • 2 GE AC1300 • 1 FE LAN · 48 Users •96 Users PoE Out • 80 Users • 48 Users • 2x2 MIMO 80 Users **RAP6202(G) RAP2200(F) RAP2200(E) RAP1200(P) RAP1200(F)**

Indoor

Outdoor

Build Ultra-fast Wi-Fi Network for the Future



RG-RAP2260(E)

AX3200 Multi-G Dual-Band Indoor Access Point



3202Mbps Throughput



2.4G: 4x4 5G: 4x4



2.5GE Port



512 Max Users



Reyee AP Mesh

274% FASTER*



Reyee Wi-Fi 6 Flag Ship High-Density Access Point

Installation Scenario:



Corridor



Banquet Hall



Dinning Hall



Meeting Room

RG-RAP2260(G)

AX1800 Dual-Band Indoor Access Point





2.4G: 2x2

5G: 2x2



1775Mbps Throughput



2 *GE Ports



100 Recommended /512 Max Users



Application Scenario:



Office



Hotel



Super Market



Restaurant

Cost-effective Wi-Fi 6 Access Point

*Compared with RG-AP720-L

Better Multi-User Experience in High-Density Scenarios Performance upgraded, support client connections over 500. Users -

RAP2200 Series—— Killer Indoor AP




802.11ac Wave2



Self-organizing Network



MU-MIMO



Layer 3 Roaming



Dual-LAN



Cloud Management



RG-RAP2200(E)



RG-RAP2200(F)





Reyee Indoor Access Points









	RG-RAP2260(E)	RG-RAP2260(G)	RG-RAP2200(E)	RG-RAP2200(F)
Protocol	802.11ax (Wi-Fi 6)	802.11ax (Wi-Fi 6)	802.11ac Wave2	802.11ac Wave2
Throughput	3202Mbps	1775Mbps	1267Mbps	1267Mbps
МІМО	4x4	2x2	2x2	2x2
Client Capacity	512	512	110	110
Recommended Client	120	100	80	48
Network Ports	1, 2.5GE ; 1, GE	2, GE	2, GE	2, FE
Free Cloud Management	\checkmark	\checkmark	$\sqrt{}$	
Reyee AP Mesh	$\sqrt{}$	$\sqrt{}$		No
Warranty	3 Years	3 Years	3 Years	3 Years



Comparison – Indoor Wi-Fi 6

3 Years



Warranty









Model	RG-RAP2260(G)	RG-RAP2260	RG-RAP2260(E)	RG-RAP2260(H)
Protocol	802.11ax (Wi-Fi 6)	802.11ax (Wi-Fi 6)	802.11ax (Wi-Fi 6)	802.11ax (Wi-Fi 6)
МІМО	2x2 @2.4 GHz 2x2 @5 GHz	2x2 @2.4 GHz 2x2 @5 GHz	4x4 @2.4 GHz 4x4 @5 GHz	4x4 @2.4 GHz 4x4 @5 GHz
Wireless Throughput	1.77Gbps	2.97Gbps	3.2Gbps	5.95Gbps
Client Capacity	512	512	512	512
Recommended Client	100	110	120	130
2.5GE Support	NO	YES	YES	YES
Network Ports	2 x GE	1 x 2.5GE, 1 x GE	1 x 2.5CE, 1 x GE	2 x 2.5GE
PoE - Standard	802.3at	802.3at	802.3at	802.3bt
Free Cloud Management	TRUE	TRUE	TRUE	TRUE
Self-organizing Network	YES	TRUE	TRUE	TRUE
Standalone Portal	YES	YES	YES	YES

3 Years

Reyee Wi-Fi 6 Outdoor AP

AX1800 Dual-Band Outdoor Access Point



2.4GHz: 2x2 5GHz: 2x2



1775Mbps Throughput



1 SFP 1 GE Port



IP68, 6KV -30°C ~ 65 °C



Reyee AP Mesh

Installation Scenario:



Swimming Pool



Parking



Beach



Garden



- 2 * GE Ports
- -30°C ~ 65 °C



RG-RAP6260(G)

- 1 SFP+1 GE Port
- -40°C ~ 65 °C



Comparison – Outdoor Wi-Fi 6











_		
IIV.		
111		
	<u>S.</u>	

Protocol

MIMO

Wireless Throughput

Client Capacity

Recommended Client

Protection Level

Network Ports

PoE - Standard

Operating Temperature

Antenna Type

Reyee Mesh

Free Cloud Management

Warranty

RG-RAP6260(H)

802.11ax (Wi-Fi 6)

4x4 @2.4 GHz 4x4 @5 GHz

5.95Gbps

512

130

IP68

1 x SFP, 1 x 2.5GE

802.3bt

-40°C ~ 65 °C

Omni-directional

TRUE

3 Years

RG-RAP6262

802.11ax (Wi-Fi 6)

2x2 @2.4 GHz 2x2 @5 GHz

2.97Gbps

512

110

IP68

1 x SFP, 1 x GE

802.3at

-30°C ~ 65 °C

Omni-directional

TRUE

TRUE

3 Years

RG-RAP6262(G)

802.11ax (Wi-Fi 6)

2x2 @2.4 GHz 2x2 @5 GHz

1.77Gbps

256

100

IP68

2 x GE

802.3at

-30°C ~ 65 °C

Omni-directional

TRUE

TRUE

3 Years

RG-RAP6260(G)

802.11ax (Wi-Fi 6)

2x2 @2.4 GHz 2x2 @5 GHz

1.77Gbps

256

100

IP68

1 x GE, 1 x SFP

802.3at

-40°C ~ 65 °C

Omni-directional

TRUE

TRUE

3 Years

Reyee Wall-Mounted AP



RG-RAP1200(P)

- 802.11ac Wave2
- 1267Mbps
- 1 *GE Uplink Port
- 4 *GE LAN Ports
- 1 * PoE Out
- Reyee AP Mesh





RG-RAP1200(F)

- 802.11ac Wave2
- 1267Mbps
- 1 *FE Uplink Port
- 1 *FE LAN Port
- 86 Standard Mount

One Click to Optimize, Get Better Wi-Fi Experience

The WIO (Wi-Fi Intelligent Optimization) technology allows you to optimize wireless network by one click.



Reyee AP Mesh - Less Wiring, More Relaxing



Flexibly Add Point


 Easy to eliminate Wi-Fi blackspots by Reyee AP in multiple scenarios.(Support all Reyee series AP except 3 models*)

Easily Setup

- Easily setup up with few clicks in APP.
- Plug and play, mesh automatically.
- · Max. 3 hops supported.

Layer 3 Roaming, Smooth Transition

Roam smoothly between Layer 3 networks with non-interruption.




Reyee Wireless Mapping

Wall







Outdoor



RG-RAP2200(E) Product Sales Guide



Introduction of Products

- Revee 11ac Wave 2 indoor ceiling AP
- 50-Meter radius coverage(open area) with omni-directional(all-direction) antenna
- 1267Mbps, 5G+2.4G dual band, 2 RJ45 GE(1000Mbps) ports. PoE.
- Recommend 80 concurrent users

Battle Card

Feature	RAP2200(E)	UAP-AC-LR	EAP225
11ac Wave1/2	Wave 2	Wave 1	Wave 2
Ports	2 GE	1 GE	1GE
Roaming	L3+L2 Roaming	L2 Roaming	L2 Roaming
Cloud Managed	Cloud/Free of charge	Buy controller at \$179	Buy controller
Warranty	3 Years	1 Year	3 Years
SI Price	\$ 55	\$ 70	\$ 75

Beyond Networks



Scenario Examples

TBC

RG-RAP2200(F) Product Sales Guide



Introduction of Products

- Reyee 11ac Wave 2 indoor ceiling AP
- 50-Meter radius coverage(open area) with omni-directional(all-direction) antenna
- 1267Mbps, 5G+2.4G dual band, 2 RJ45 **FE(100Mbps)** ports. PoE.
- Recommend 48 concurrent users

Battle Card

Feature	RAP2200(F)	UAP-AC-LR	EAP225
11ac Wave1/2	Wave 2	Wave 1	Wave 2
Ports	2 FE	1 GE	1GE
Roaming	L3+L2 Roaming	L2 Roaming	L2 Roaming
Cloud Managed	Cloud/Free of charge	Buy controller at \$179	Buy controller
Warranty	3 Years	1 Year	3 Years
SI Price	\$ 42	\$ 70	\$ 75

Beyond Networks



Scenario Examples


TBC

RG-RAP2200(E)/(F) Product Sales Guide



Better Multi-User Experience with Wave2

Better performance via Wave 2's MU-MIMO. Wave1's MIMO only serves one user at a time. While Wave2 can serve multiple users.



Test Video
RAP2200(E) VS UAP-AC-LR - 20% Higher experience score
when serving 30 concurrent HD video users.

WARPACTURN and UAP AC-LITE with same concurrent user
Beyond Networks

RG-RAP2200(E)/(F) Product Sales Guide




Non-stop Wi-Fi Traffic even Moving in Campus. L3 Roaming Helps.

RAP2200(E)/(F) support L3 roaming, enables non-interrupted Wi-Fi traffic between buildings or floors. Enhance user roaming experience on campus projects.



L3 Roaming between buildings




3-Min-How-To Video How-to Tell Advantage of Reyee L3 Roaming

L3 Roaming between floors

RG-RAP2200(E)/(F) Product Sales Guide



Additional LAN2 GE/FE port on RAP2200(E)/(F)



1GE port only for uplink on UAP-AC-Lite

FAQ

Q: UAP-AC-LR and EAP225 are with 450Mbps/3x3 MIMO on 2.4GHz, better than 2200(E)'s 400Mbps/2x2 MIMO? A: 2.4GHz is the 'trash' band, full of contention and interference. Even with 3X3 MIMO and 50Mbps higher theoretical data, does little help to actual performance.

2 LAN Ports- Extra Port Saves Cost

2GE ports available on RAP2200(E). One additional port available for connection to an IP camera or IP phone. Saves cost without extra cabling or switch port occupancy. While RAP2200(F) provides 2 FE ports.

Competitive Price and Better Warranty

For UBNT-AC-LR. At 30%(2200(E)) or 45% (2200(F)) lower price, buy a Wave2 AP instead of a Wi-Fi 5(UAP-AC-LR). 2 More years warranty provided with RAP2200(E/F), provides much better experience to customers.

For EAP225. At **35%(2200(E))** or **50% (2200(F))** lower price, can afford 2 APs instead of 1 with 2200(F).

Q: How to make choice between your RAP2200(E) and RG-AP720-L?
A: AP720-L supports 2 times concurrent user to RAP2200(E). If compete with Cisco, Ruckus or Aruba, suggestion AP720-L. If have limit budget or compete with TP-Link, choose RAP2200(E)

RG-RAP6202(G) Product Sales Guide

Introduction of Products

- Reyee 11ac Wave 2 outdoor AP, with UFO shape, pole-mount/wall-mount
- 300-Meter radius coverage(open area) with omni-directional(all-direction) antenna
- 1167Mbps, 5G+2.4G dual band. 2 GE(1000Mbps) ports. PoE.
- Recommend 96 concurrent users

Battle Card

Feature	RAP6202(G)	UAP-AC-M	EAP225-Outdoor
Water Proof	IP68	n/a	IP65
11ac Wave1/2	Wave 2	Wave 1	Wave 2
Ports	2 GE	1 GE	1 GE
Tx Power	27dBm	20dBm	27dBm
Roaming	L3+L2 Roaming	L2 Roaming	L2 Roaming
Cloud Managed	Cloud/Free of charge	Buy controller at \$179	Buy controller
Warranty	3 Years	1 Year	3 Years
SI Price	\$ 114	\$110	\$122



Scenario Examples

• TBC

RG-RAP6202(G) Product Sales Guide



Stronger Signal at ALL Directions

To UAP-AC-M. Stronger signal by 400mW better on transmit power. 2 Times on direct distance and 4 Times lager on coverage area to UAP-AC-M.

While with UFO shape and all-direction **internal** antennas, easy for installation spot choice, while **don't have worry external antenna might get stolen one day.**



Better Water-proof Design

To EAP225-Outdoor. Much higher water and dust proof with IP68 rating on RAP6202(G). EAP225 only has IP65. IP stands for Ingress Protection, set by IEC. IPXX. The greater number XX is, the better proof you have. IP68 means AP can stay working at 1-meter deep water. IP65 means AP only can be protected against 3 minutes of direct water spray.





Better Performance


To UAP-AC-M. Better performance via Wave 2's MU-MIMO. Wave1's MIMO only serves one user at a time. While Wave2 can serve multiple users

RG-RAP6202(G) Product Sales Guide



1 More Down Link Ports

Have CCTV IP camera on the same pole? RAP6202(G) provides **1 more down link ports**. **Saves cost** without extra cabling or switch port occupancy.



2 GE ports on RAP6202(G)



INNOVATION
Beyond Networks

Good Price and Better Warranty

For UAP-AC-M. At a similar price, buy a better signal, better water/dust-proof Wave2 AP instead of a Wave1(UAP-AC-M). **2 More years** warranty provided with RAP6202(G), provides much better experience to customers.

FAQ

TBC

RG-RAP1200(P) Product Sales Guide



Introduction of Products

- Reyee 11ac Wave 2 indoor wall-mount AP
- 30-Meter radius coverage(open area) with omni-directional(all-direction) antenna
- 1267Mbps, 5G+2.4G dual band. 1 GE(1000Mbps) port uplink. PoE.
- 4 RJ45 GE down-link ports including 1 PoE-Out port
- Recommend 80 concurrent users

Battle Card

Feature	RAP1200(P)	UAP-IW	EAP225-Wall
11ac Wave1/2	Wave 2 Wave 1		Wave 2
Ports	5 GE	3 GE	4GE
Data Rate	1267Mbps	1167Mbps	1167Mbps
Roaming	L3+L2 Roaming	L2 Roaming	L2 Roaming
Cloud Managed	Cloud/Free of charge	Buy controller at \$179	Buy controller
Warranty	3 Years	1 Year	3 Years
SI Price	\$ 72	\$ 80	\$ 74





Scenario Examples

TBC

RG-RAP1200(F) Product Sales Guide



Introduction of Products

- Reyee 11ac Wave 2 indoor wall-mount AP
- 30-Meter radius coverage(open area) with omni-directional(all-direction) antenna
- 1267Mbps, 5G+2.4G dual band. 1 FE(100Mbps) port uplink. 1FE port down link. PoE.
- Recommend 40 concurrent users





Battle Card

Feature	RAP1200(F)	EAP115-Wall
Band	5G+2.4G (11ac Wave2)	2.4G 11n
Data Rate	1267Mbps	300Mbps
Roaming	L3+L2 Roaming	L2 Roaming
Cloud Managed	Cloud/Free of charge	Buy controller
Warranty	3 Years	3 Years
SI Price	\$ 32	\$ 30

Scenario Examples

TBC

INNOVATION

Beyond Networks

RG-RAP1200(P) Product Sales Guide



Better Performance

1267Mbps to 1167Mbps with **100Mbps** more on data rate. Faster performance with higher speed for users. To UAP-IW. **Better performance via Wave 2's MU-MIMO**. Wave1's MIMO only serves one user at a time. While Wave2 can serve multiple users



Have IPTV? IP phone? Or a laptop/PC/printer? RAP1200(P) provides 1~2 more down link ports. **Saves cost** without extra cabling or switch port occupancy.





Good Price and Better Warranty

For UAP-IM. At **18% lower price**, buy a **Wave2 AP** instead of a Wi-Fi 5(UAP-IM). **2 More years** warranty provided with RAP1200(P), provides much better experience to customers.

RG-RAP1200(F) Product Sales Guide

Side look on RAP1200(F)

Buy 11ac Wave2 AP at 11n Price

At similar price with EAP115, you get an 11ac Wave2 AP instead of a 11n one. Much better user experience with 5G band available.

Thinner than 11n

RAP1200(F) is even **2mm** thinner than EAP115 on front cover size. More good looking when installed on walls of home or hotels.

FAQ

Q: How can we install these 86mm size AP into 120mm socket?

A: If using 120mm socket, you can choose universal mount kit for different sized/standard junction boxes.

However, appearance with such mount kit may differ from 86mm sized ones.





Side look on EAP115

RG-RAP6260(G) Product Sales Guide



Introduction of Products

- Reyee Wi-Fi 6 Outdoor AP
- 1775Mbps, 5G+2.4G dual band, RJ45(PoE) +SFP uplink
- Omni-directional antenna, IP68, pole/wall-mount

Battle Card

Feature	RG-RAP6260(G)	UBNT (UAP-AC-M-PRO)
Water Proof	IP68 Any-direction mounting	n/a Downward mounting only
Wi-Fi 6/5	Wi-Fi 6	Wi-Fi 5
Concurrent Users	Max 512	Max 250
Tx Power	26dBm	22dBm
Cloud Managed	Cloud/Free of charge	Buy controller at \$179
Warranty	3 Years	1 Year
SI Price	\$ 186	\$ 168




Scenario Examples

TBC

RG-RAP6260(G) Product Sales Guide





Wi-Fi 6 Brings 2X Max Users

Max **512** concurrent users. **2 Times** to UBNT's AC-M-Pro. Faster speed, massive concurrent user and low latency Wi-Fi experience for outdoor area.


Better Water-proof Design

RAP6260(G)'s water-proof connectors design **enables any-direction mounting**. Easy for installation spot choice.


While AC-M-PRO only supports downward mounting because of no connector. IP68 protection, -40°C ~ 65 °C operating temperature, V0 anti-flaming, 6KV lighting proofy. Steady in any harsh environment.

Beyond Networks

Water-proof connectors of RAP6260(G)



No direction limit of mounting



No connectors on AC-M-PRO




Only DOWNWARDS mounting

RG-RAP6260(G) Product Sales Guide



Larger Signal Coverage

4dBm higher on transmit power. 30~50% Better signal strength client receives at the same spot.
20% Larger area coverage. Less AP required with signals guaranteed.



SFP port for long distance

Sometimes SI is not quite sure of the positioning of the AP. So depend on actual cable distance, either UTP(<100 meters) cable or fiber(>=100 meters) might be required. With SFP port on 6260(G), we provide SI with extra options.

SFP Port on RAP6260(G)

FAQ

Competitive Price and Better Warranty

UBIQUITI distributor or reseller, one year after the date of shipmer such authorized distributor or reseller. UBIQUITI'S sole and exclusive year the foregoing warranty shall be for UBIQUITI at its discretive

At **similar price**, buy a **Wi-Fi 6 AP**(RAP2260(G)) instead of a Wi-Fi 5(UAP-AC-M-PRO). **2 More years** warranty provided with RAP6260(G), better protects customer investment.

A: 3X3-M/MQ indeed but still working at Wi-Fi 5. With Wi-Fi 6's OFDMA/1024QAM/MU-MIMO, even 2X2 MIMO we have higher performance than AC-M-PRO)

RG-RAP2260(E) Product Sales Guide



Introduction of Products

- Reyee Wi-Fi 6 high-density indoor AP
- 3200Mbps, 4x4, 5G+2.4G dual band, 2.5G POE + 1G RJ45 uplink
- Max 512, recommended 120 users, for bar, conference hall, restaurant, etc.

Battle Card

Feature	RG-RAP2260(E)	UBNT (U6-LR)
Max Speed	3200Mbps	3000Mbps
Concurrent Users	Max 512	Max 300
Uplink Port	1* 2.5GE PoE IN 1* GE RJ45	1* GE PoE IN
Cloud Managed	Cloud/Free of charge	Buy controller at \$179
Warranty	3 Years	1 Year
SI Price	\$ 154	\$ 179



Scenario Examples


TBC


INNOVATION

Beyond Networks

RG-RAP2260(E) Product Sales Guide







Faster Speed with Multi-G & AX3200

RAP2260(E) **2.5G** port allows more than **2.5X** Internet speed than UBNT U6-LR. Because the U6-LR uplink only 1*GE, it's internet speed limited by 1Gbps only.

As tested in lab, compare with U6-LR get only 928Mbps pass through speed, the RAP2260(E) can get 2120Mbps, 2.28 times higher.

Competitive Price and Better Warranty

At 15% lower price, buy RAP2260(E) instead of U6-LR. 2 More years warranty provided with RAP2260(E), and also with higher performance, better protects customer investment.

FAQ

Q: It supports 2.5G port, but Reyee don't have 2.5G switch? A: Yes, the 2.5G switch has not been widely applied now, our Reyee multi-G Switch is also in planning. You can see, the RG-RAP2260(E) is designed for future, to protect your investment. You don't need to upgrade your network any more in following several years.

RG-RAP2260(G) Product Sales Guide



Introduction of Products

- Reyee cost-effective Wi-Fi 6 indoor AP, enjoy Wi-Fi 6 with Wi-Fi 5 price.
- 1775Mbps, 5G+2.4G dual band, dual GE RJ45 uplink
- Max 512, recommended 100 users.

Battle Card

Feature	RG-RAP2260(G)	UBNT (U6-Lite)
Max Speed	Wi-Fi 6 1775Mbps	Wi-Fi 6 1500Mbps
Concurrent Users	Max 512	Max 300
LAN Port	2* GE Ports	1* GE Port
Cloud Managed	Cloud/Free of charge	Buy controller at \$179
Warranty	3 Years	1 Year
SI Price	\$ 88	\$ 86



Scenario Examples

TBC

INNOVATION


Beyond Networks


RG-RAP2260(G) Product Sales Guide



Faster Speed & More Concurrent Users

Speed up to 1775Mbps, 275Mbps higher. Max 512 concurrent users. 1.7 Times to UBNT's U6-Lite. Faster speed, more concurrent user and low latency Wi-Fi experience.







2 LAN Ports - Extra Port Saves Cost

2GE ports available on RAP2260(G). 1 more down link port is available for connection to an IP camera or IP phone.

Saves cost without extra cabling or switch port occupancy.

Competitive Price and Better Warranty

At similar price, buy RAP2260(G) instead of U6-Lite. **2 More years** warranty provided with RAP2260(G), and also with higher performance, better protects customer investment.

Beyond Networks

FAQ

Q: What's the difference with RG-AP820-L

A: RG-AP820-L has better performance for more budget project.

RG-RAP2260(G) with similar performance but cost effective.

	Reyee	UBNT	Aruba Instant On	TP-Link
				•
	RG-RAP1200(F)	No Model	No Model	EAP115-Wall
Key Specification				
Protocol	802.11ac Wave2, 1267Mbps	N/A	N/A	802.11n, 300Mbps
Ports	2 FE LAN	N/A	N/A	2 FE LAN
Thickness	9.2mm	N/A	N/A	11mm
Layer 3 Roaming	✓	N/A	N/A	×
Cloud Managed	✓	N/A	N/A	On-premises controller needed
Advanced Features				
Self-organizing Network	✓	N/A	N/A	×
Warranty	3 Years	N/A	N/A	1 Years
Wi-Fi Butten	×	N/A	N/A	✓

- Reyee cost-effective wall AP.
- Auto-provision via Self-organizing network technology and saved a lot of time for installers.
- Hidden lights give customers a better sleep experience in the hotel scene.







	Reyee	UBNT	Aruba Instant On	TP-Link
				Ø rec
	RG-RAP1200(P)	UAP-IW	AP11D	EAP235-Wall
Key Specification				
Protocol	802.11ac Wave2, 1267Mbps	802.11ac, 1167Mbps	802.11ac Wave2, 1267Mbps	802.11ac Wave2, 1167Mbps
Ports	4 GE LAN, 1 GE Uplink	3 GE LAN	3 GE LAN, 1 GE Uplink	3 GE LAN, 1 GE Uplink
PoE Passthrough	~	~	~	✓
Layer 3 Roaming	~	×	✓	×
Cloud Managed	✓	On-premises controller needed	License Needed	On-premises controller needed
Advanced Features				
Self-organizing Network	✓	×	×	×
Warranty	3 Years	1 Years	2 Years	1 Years
Desktop Kit	×	×	✓	×

- RAP1200(P) build-in 4GE LAN ports. It is useful to extend the IPTV/ VOIP; PoE Out supported;
- Auto-provision via Self-organizing network technology and saved a lot of time for installers;
- Hidden lights give customers a better sleep experience in the hotel scene.







	Reyee	UBNT	Aruba Instant On	TP-Link
	RG-RAP2200(E)	UAP-AC-LR	AP11	EAP225 V3
Key Specification				
Protocol	802.11ac Wave2, 1267Mbps	802.11ac, 1317Mbps	802.11ac Wave2, 1167Mbps	802.11ac Wave2, 1317Mbps
Ports	2 GE LAN	1 GE LAN	1 GE LAN	1 GE LAN
Concurrent Users	110	1	50	1
Layer 3 Roaming	✓	×	~	×
Cloud managed	✓	On-premises controller needed	License Needed	On-premises controller needed
Advanced Features				
Self-organizing Network	✓	×	×	×
Warranty	3 Years	1 Years	2 Years	1 Years
BLE Connection	×	N/A	✓	N/A

- Provide good wireless Internet experience for high-density scenario.
- Built-in 2 *GE LAN ports. It is useful to extend the camera or other IP-based devices.
- Auto-provision via Self-organizing network technology and saved a lot of time for installers.







	Reyee	UBNT	Aruba Instant On	TP-Link
	RG-RAP2200(F)	UAP-AC-Lite	AP11	EAP225 V2
Key Specification				
Protocol	802.11ac Wave2, 1267Mbps	802.11ac, 1167Mbps	802.11ac Wave2, 1167Mbps	802.11ac, 1167Mbps
Ports	2 FE LAN	1 GE LAN	1 GE LAN	1 GE LAN
Concurrent Users	110	1	50	1
Layer 3 Roaming	✓	×	✓	×
Cloud managed	✓	On-premises controller needed	License Needed	On-premises controller needed
Advanced Features				
Self-organizing Network	✓	×	×	×
Warranty	3 Years	1 Years	2 Years	1 Years
BLE Connection	×	N/A	~	N/A

- Provide good wireless Internet experience for high-density scenario with cost-effective AP.
- Built-in 2 *GE LAN ports. It is useful to extend the camera or other IP-based devices.
- Auto-provision via Self-organizing network technology and saved a lot of time for installers.







	Reyee	UBNT	Aruba Instant On	TP-Link
			name of the second	
	RG-RAP2260(G)	U6-Lite	AP22	EAP620 HD
Key Specification				
Protocol	Wi-Fi 6, 1775Mbps	Wi-Fi 6, 1500Mbps	Wi-Fi 6, 1775Mbps	Wi-Fi 6, 1775Mbps
Ports	2 GE LAN	1 GE LAN	1 GE LAN	1 GE LAN
Concurrent Users	512	300	75	1
Cloud managed	~	On-premises controller needed	License Needed	On-premises controller needed
Advanced Features				
Self-organizing Network	~	×	×	×
Warranty	3 Years	1 Years	2 Years	1 Years
BLE Connection	×	N/A	✓	N/A

- Provide good speed, more concurrent user and low latency Wi-Fi experience.
- One more down link port is available for connection to an IP camera or IP phone.
- Good warranty.







	Reyee	UBNT	Aruba Instant On	TP-Link
				(9)
	RG-RAP2260(E)	U6-LR	No Model	EAP660 HD
Key Specification			N/A	
	2.4GHz: Wi-Fi 6 4x4	2.4GHz: Wi-Fi 4 4x4		Wi-Fi 6
Protocol	5GHz: Wi-Fi 6 4x4	5GHz: Wi-Fi 6 4x4	N/A	
Wireless Rate	3202Mbps	3000Mbps	N/A	3550Mbps
Ports	2.5GE LAN, 1 GE LAN	1 GE LAN	N/A	2.5GE LAN
Concurrent Users	512	300	N/A	1
Cloud Managed	✓	On-premises controller needed	N/A	On-premises controller needed
Advanced Features				
Self-organizing Network	~	×	N/A	×
Warranty	3 Years	1 Years	N/A	1 Years
BLE Connection	×	N/A	N/A	N/A

- Provide good speed, more concurrent user and low latency Wi-Fi experience.
- One more down link port is available for connection to an IP camera or IP phone.
- Good warranty.







	Reyee	UBNT	Aruba Instant On	TP-Link
	RG-RAP2260	U6-LR	No Model	EAP653/650
Key Specification			N/A	
Protocol	Wi-Fi 6, AX3000	Wi-Fi 6, AX3000		Wi-Fi 6, AX3000
Ports	2.5GE LAN, 1 GE LAN	1 GE LAN	N/A	1 GE LAN
Concurrent Users	512	300	N/A	1
Cloud managed	✓	On-premises controller needed	N/A	On-premises controller or device license fee needed
			N/A	
Advanced Features			N/A	
Self-organizing Network	~	×		×
Warranty	3 Years	1 Years	N/A	1 Years
BLE Connection	×	N/A	N/A	N/A

- Same wireless performance, faster to Internet with 2.5GE port uplink, invest in now and the future.
- Support more concurrent connections, more connected devices can enjoy faster speeds
- Free cloud management, and good warranty. Save maintenance cost.







	Reyee	UBNT	Aruba Instant On	TP-Link
	RG-RAP2260(H)	N/A	AP25	EAP670
Key Specification				
Protocol	Wi-Fi 6, AX6000	N/A	Wi-Fi 6, AX5400	Wi-Fi 6, AX5400
Ports	2 x 2.5GE LAN	N/A	1 x 2.5GE LAN	1 x 2.5GE LAN
Concurrent Users	512	N/A	100+	1
MIMO	2.4GH: 4x4 ; 5GH: 4x4	N/A	2.4GH: 2x2; 5GH: 4x4	2.4GH: 2x2; 5GH: 4x4
Cloud managed	~	N/A	License Needed	On-premises controller or device license fee needed
Advanced Features				
Self-organizing Network	✓	N/A	×	×
Warranty	3 Years	N/A	2 Years	1 Years
BLE Connection	×	N/A	~	N/A

- Enjoy faster wireless, and faster Internet with dual 2.5GE port(support aggregation), invest in now and the future.
- Support more concurrent connections, more connected devices can enjoy faster speeds
- Dual radio 4x4 MU-MIMO, better experience in high-density scenarios.
- Free cloud management, and good warranty. Save maintenance cost.







	Reyee	UBNT	Aruba Instant On	TP-Link
	RG-RAP6202(G)	UAP-AC-M	AP17	EAP225-Outdoor
Key Specification				
Protocol	802.11ac Wave2, 1267Mbps	802.11ac Wave1, 1167Mbps	Wi-Fi 5, 1167Mbps	802.11ac Wave1, 1167Mbps
Ports	2 GE LAN	1 GE LAN	1 GE LAN	1 GE LAN
Concurrent Users	110 Max / 96 Recommended	250 / -	50	- / 60-80
Cloud Managed	✓	On-premises controller needed	License Needed	On-premises controller needed
Protection Level	IP68	Must downward mounting	IP55	IP65
Advanced Features		Ç		
Self-organizing Network	✓	×	×	×
Warranty	3 Years	1 Years	2 Years	3 Years
Roaming	L2 + L3 Roaming	L2 Roaming	~	L2 Roaming

- Good speed, and more concurrent users are supported for outdoor area.
- IP68 water-proof connectors design enables any-direction mounting. Easy for installation spot selection.
- One more down link ports. Saves cost without extra cabling or switch port occupancy.







	Reyee	UBNT	Aruba Instant On	TP-Link
	RG-RAP6260(G)	No Model	No Model	EAP610-Outdoor
Key Specification				
Protocol	Wi-Fi 6, 1775Mbps	N/A	N/A	Wi-Fi 6, 1775Mbps
Ports	1 GE LAN, 1 SFP LAN	N/A	N/A	1 GE LAN
Concurrent Users	512	N/A	N/A	1
Cloud managed	~	N/A	N/A	On-premises controller needed
Protection Level	IP68	N/A	N/A	IP67
Advanced Features		N/A	N/A	
Self-organizing Network	~	N/A	N/A	×
Warranty	3 Years	N/A	N/A	3 Years
SNMP Management	×	N/A	N/A	✓

- Good speed, massive concurrent user and low latency Wi-Fi experience for outdoor area.
- IP68 water-proof connectors design enables any-direction mounting. Easy for installation spot selection.
- SFP port for long distance installation and better warranty.







	Reyee	UBNT	Aruba Instant On	TP-Link
	RG-RAP6262(G)	UAP-AC-M-PRO	AP17	EAP610-Outdoor
Key Specification				
Protocol	Wi-Fi 6, 1775Mbps	Wi-Fi 5, 1750Mbps	Wi-Fi 5, 1167Mbps	Wi-Fi 6, 1775Mbps
Ports	2 GE LAN	1 GE LAN	1 GE LAN	1 GE LAN
Concurrent Users	256	250	50	1
Cloud managed	~	On-premises controller needed	License Needed	On-premises controller needed
Protection Level	IP68	Must downward mounting	IP55	IP67
Advanced Features		ŭ		
Self-organizing Network	~	×	×	×
Warranty	3 Years	1 Years	2 Years	3 Years
SNMP Management	×	N/A	✓	~

- Good speed, massive concurrent user and low latency Wi-Fi experience for outdoor area.
- IP68 water-proof connectors design enables any-direction mounting. Easy for installation spot selection.
- One more down link ports. Saves cost without extra cabling or switch port occupancy.







	Reyee	UBNT	Aruba Instant On	TP-Link
	RG-RAP6262	No Model	No Model	EAP650-Outdoor
Key Specification				
Protocol	Wi-Fi 6, AX3000	N/A	N/A	Wi-Fi 6, AX3000
Ports	1 x SFP + 1 x GE	N/A	N/A	1 GE LAN
Concurrent Users	512	N/A	N/A	1
Cloud managed	~	N/A	N/A	On-premises controller needed
Protection Level	IP68	N/A	N/A	IP67
Advanced Features		N/A	N/A	
Self-organizing Network	~	N/A	N/A	×
Warranty	3 Years	N/A	N/A	3 Years
SNMP Management	×	N/A	N/A	~

- Support more concurrent connections, more connected devices can enjoy faster speeds
- IP68 water-proof connectors design enables any-direction mounting. Easy for installation spot selection.
- SFP port for long distance installation, support up to 20km transmission from datacenter with single mode fiber.







	Reyee	UBNT	Aruba Instant On	TP-Link
	RG-RAP6260(H)	U6-MESH	No Model	No Model
Key Specification				
Protocol	Wi-Fi 6, AX6000	Wi-Fi 5, AX5400	N/A	N/A
Ports	1 x 2.5GE, 1 x SFP	1 GE LAN	N/A	N/A
Concurrent Users	512	300+	N/A	N/A
MIMO	2.4GH: 4x4; 5GH: 4x4	2.4GH: 2x2; 5GH: 4x4	N/A	N/A
Cloud managed	~	On-premises controller needed	N/A	N/A
Protection Level	IP68	IPX5	N/A	N/A
Self-organizing Network	~	×	N/A	N/A
Warranty	3 Years	1 Years	N/A	N/A
SNMP Management	×	N/A	N/A	N/A

- Enjoy faster wireless, and faster Internet with 2.5GE port, invest in now and the future.
- IP68 water-proof connectors design enables any-direction mounting. Easy for installation spot selection.
- SFP port for long distance installation, support up to 20km transmission from datacenter with single mode fiber.









THANKS

